(19) World Intellectual Property Organization

International Bureau



. I BODA BURKUR NI BURNE NGA BOAN BARK BAN EN HI KU BARK BURNE NA BURNE BAN BURNE BARK

(43) International Publication Date 16 June 2005 (16.06.2005)

PCT

(10) International Publication Number WO 2005/055406 A1

- (51) International Patent Classification⁷: H04R 1/04, 3/00, 19/00
- H02M 3/07,
- H04K 1/04, 3/00, 19/00
- (21) International Application Number: PCT/DK2004/000837
- (22) International Filing Date: 1 December 2004 (01.12.2004)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/525,826


1 December 2003 (01.12.2003) U

- (71) Applicant (for all designated States except US): AUDIOA-SICS A/S [DK/DK]; Langebjergvænget 10A, st., DK-4000 Roskilde (DK).
- (71) Applicant and
- (72) Inventor (for all designated States except US): DERUG-INSKY, Michael [DK/DK]; Batzkes Bakke 13A, DK-3400 Hillerød (DK).

- (74) Agent: ZACCO DENMARK A/S; Hans Bekkevolds Allé 7, DK-2900 Hellerup (DK).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: MICROPHINE WITH VOLTAGE PUMP



(57) Abstract: An integrated circuit (102) configured to provide a microphone output signal, comprising: a preamplifier (108) coupled to receive an input signal, generated by a first microphone member that is movable relative to a second microphone member; and a voltage pump (104) to provide a bias voltage to either microphone member.

WO 2005/055406 A1



Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.